



## DAY/NIGHT IR VANDAL RESISTANT DOME CAMERA Technical Specification

<b>Image Pick-Up Device</b>	1/3" SONY SUPER HAD CCD
<b>TV System</b>	NTSC / PAL
<b>Pixels</b>	NTSC = 510(H)X 492(V) PAL = 500(H)X 582(V)
<b>Scanning System</b>	2 :1 Interlaced
<b>Sync System</b>	Internal (DC) / Line Lock (AC) - Option
<b>Resolution</b>	420TV Line
<b>Minimum Illumination</b>	0.00Lux
<b>S/N Ratio</b>	More than 50 dB
<b>Gamma Characteristic</b>	0.45
<b>Video output</b>	1.0Vp-p 75 ohm Composite
<b>Electronic shutter Speed</b>	NTSC : 1/60 ~ 1/100,000 sec PAL : 1/50 ~ 1/100,000 sec
<b>Power Supply</b>	DC12V or AC 24V Dual (Option)
<b>Power Consumption</b>	300 mA
<b>Lens</b>	4 ~ 9mm
<b>Operational Temperature</b>	-10Deg ~ +50 Deg C RH95% Max
<b>Storage Temperature</b>	-20Deg ~ +60 Deg C RH95% Max
<b>Weight</b>	Appx. 500g