



True Mechanical Day/Night(ICR)

Technical Specification

DETAILS	NTSC	PAL
Imaging Sensor	1/3" Color Sony Super HAD CCDII	
Effective Pixels	NTSC: 768(H) X 494(V) PAL: 752(H) X 582(V)	
Scanning System	2:1 Interlace	2:1 Interlace
Synchronization	Internal / Line Lock	
Resolution	550TVL(Color) / 600TVL(B/W)	
Video Output	1Vp-p 75, Negative	
S/N Ratio	More Than 52dB (AGC Off)	
Min. Illumination	0.15 Lux (F1.2)	
Gamma	r=0.45	
White Balance	ATW/AWC/Manual/Outdoor/Indoor	
Shutter Speed	1/60~1/120,000	1/50~1/120,000
Day & Night	True Day & Night	
Lens	3.5 ~ 16mm Varifocal Lens	
LED	IR LED 70pcs	
Power Supply	Dual Power	
Current Consumption	Max. 800mA	
Fan & Heater	Built in Fan/ Optional Heater	
Operation Temp.	-10°C ~ 50°C	
Storage Temp/Humidity	-20°C ~ 60°C / 20% ~ 90%	
Dimension	130.2(W)x216.2(H)x430.4(D)	
Weight	Approx. 2.3Kg	